

WHITEMAN TOWABLE PLASTER/MORTAR MIXERS

Features

- Hydraulic-drive options on 12-cu. ft. models
- Available in 4.5-, 6.3-, 7-, 9- and 12-cu. ft. models
- Heavy-duty safety grate with built-in bag cutter
- 13" tires for safe towing
- Forklift pockets
- Steel models offer durable drum up to 3/16" thick
- Polyethylene drums simplify cleanup while resisting rust and dents



Polyethylene Drum



Steel Drum

Technical specifications

STEEL MODEL	POLY MODEL	CAPACITY CU FT (L)	ENGINE	HP (KW) ¹	DRIVE
WM45H*	—	4.5 (113)	HONDA	3.5 (113)	V-BELT/GEAR
WM63H8	—	6.3 (178)	HONDA	7.9 (5.8)	V-BELT/GEAR
WM63H5	—	6.3 (178)	HONDA	4.8 (3.6)	V-BELT/GEAR
WM63E	—	6.3 (178)	115/230V,1Ø	1.5 (1.1)	V-BELT/GEAR
WM70SE	WM70PE	7 (198.2)	115/230V,1Ø	1.5 (1.1)	V-BELT/GEAR
WM70SH5	WM70PH5	7 (198.2)	HONDA	4.8 (3.6)	V-BELT/GEAR
WM70SH8	WM70PH8	7 (198.2)	HONDA	7.9 (5.8)	V-BELT/GEAR
WM90SE	WM90PE	9 (254.9)	230V,1Ø	3.0 (2.2)	V-BELT/GEAR
WM90SH8	WM90PH8	9 (254.9)	HONDA	7.9 (5.8)	V-BELT/GEAR
WM120SHHD	WM120PHD	12 (339.8)	HONDA	11.7 (8.7)	HYDRAULIC

*Wheelbarrow design

¹ See page 46 for details.