

# MRH800GS

Double drum, Honda GX390, 25.6" drum



Multi-quip's rugged walk-behind tandem rollers all feature advanced engineering and design satisfying the needs of the most demanding contractors.

- Hour/tachometer measures runtime and engine rpm
- Hydrostatic drive eliminates drive belts and adjustments
- Infinite variable speed control gives the operator full control with forward, reverse speeds
- External mounted vibrator assembly for easy maintenance access
- Deadman safety control stops roller when the operator takes hands off the control levers
- Large rubber shock mounts minimize drum vibration transfer to engine, hydraulic components
- Guide handle folds up 90 degrees for easy transport and storage
- Narrow profile design for less than 1 inch (25 mm) side clearance
- Dual sprinkler controls wet drum individually
- Single access maintenance cover for easy access to all hydraulic components
- Permanently lubricated bearings are maintenance free
- Built-in tie-downs on all four corners secure the roller during transport

## Unit Specifications

Compaction Force	5300 lb	23.57 kN
Frequency	3300 VPM	55.3 Hz
Travel Speed	0-2 mph	0-3 kph
Water Tank Capacity	10.6 gal	40.12 L

## Drum Specifications

Front Drum Width	25.6 in	650 mm
Rear Drum Width	25.6 in	650 mm

## Dimensions & Weights

Overall Length	105 in	2667 mm
Overall Width	27.2 in	691 mm
Overall Height	41.7 in	1059 mm
Operating Weight	1530 lb	694 kg

Notice: Features and equipment specifications are subject to change without notice.